

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G07D 3/02		A1	(11) International Publication Number: WO 96/30877
			(43) International Publication Date: 3 October 1996 (03.10.96)
(21) International Application Number: PCT/SE96/00142			(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KG, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 7 February 1996 (07.02.96)			
(30) Priority Data: 9501091-4 28 March 1995 (28.03.95) SE			
(71) Applicant (for all designated States except US): SCAN COIN AB [SE/SE]; Jägershillgatan 26, S-213 75 Malmö (SE).			
(72) Inventors; and (75) Inventors/Applicants (for US only): KNUTSSON, Jörgen [SE/SE]; Promenaden 5a, S-240 32 Flyinge (SE). LUNDGREN, Staffan [SE/SE]; Abbeåsgatan 10 c, S-214 40 Malmö (SE).			
(74) Agents: STRÖM, Tore et al.; Ström & Gulliksson AB, P.O. Box 4188, S-203 13 Malmö (SE).			


Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

In English translation (filed in Swedish).

(54) Title: DEVICE AND METHOD FOR SEPARATING FOREIGN OBJECTS FROM A MASS OF COINS



(57) Abstract

A device is used to separate foreign objects from a mass of coins between a coin intake and a coin lifting device in a coin sorting and/or counting machine. The device has a perforated drum (13; 33), which is rotatable around its longitudinal axis, is open at its respective ends and is connected at a first end to the coin intake and at a second end to the coin lifting device. The machine also has a driving device (15, 16; 35) for rotating the drum.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

DEVICE AND METHOD FOR SEPARATING FOREIGN OBJECTS FROM A MASS OF COINS

Technical field

5 The present invention relates to a device and a method for separating foreign objects from a mass of coins between a coin intake and a coin lifting device in a coin sorting and/or counting machine.

10 Description of the prior art

Today, a plurality of devices are known for coin sorting and/or counting. Such devices or machines are usually provided with a coin intake and a coin lifting device (such as a hopper), wherein the coin intake is
15 arranged to receive an incoming mass of coins and to supply this mass of coins to the coin lifting device, which establishes some sort of order among the coins in the mass, such as a sequential order, so that the coins one after another may be supplied at a proper speed to a subsequent sorting
20 and/or counting process.

Recently, such coin sorting machines and coin counting machines, which are intended to be used directly by the customers in accordance with a self-service approach, have been increasingly common. Such self-service
25 coin handling machines may be located in for instance bank offices to be used by any customer who wants to cash or deposit an unsorted mass of coins. For instance, a businessman may want to deposit his daily earnings, or a private person may bring his savings. The customer in
30 question will deposit the mass of coins in a coin intake, and then the coin handling machine will sort and count the coins received and acknowledge the amount received by means of for instance a written verification, on which the counted amount is specified.

35 A problem with self-service coin handling machines of the type described above, which has been observed by the

inventors of the present invention, is the damage or reduced performance that foreign objects in a mass of coins may cause. Previously known coin handling machines are usually provided with a separating function, wherein any
5 coin not accepted due to e.g. an incorrect currency, deformation of the coin or the like, is separated from the rest of the coins and is returned to the customer, or is confiscated by the machine as an alternative. The problem gets worse if the coin mass contains such foreign objects, which
10 as to their shape, size or the like are considerably different from coins acceptable to the machine. Examples of such foreign objects are paper clips, safety-pins, screws, nuts, hair pins, pocket fluff, etc. If such foreign objects are deposited in a coin handling machine, the risk of
15 damage to mechanical or electrical components in the machine is not negligible.

Futhermore, if the mass of coins is deposited by the customer into the coin intake in such volumes or at such a speed that the coin handling machine will not be capable of
20 processing the coin mass but will rather be over-filled, additional problems will arise.

Summary of the invention

According to the invention a device and a method have
25 been developed to eliminate or reduce the above-mentioned problems, when a mass of coins with inappropriate contents or of an inappropriate volume is supplied by a customer to a coin handling machine.

The object of invention is achieved by a device and a
30 method for separating foreign objects from a mass of coins between a coin intake and a coin lifting device in a coin sorting and/or counting machine with the features of the characterising part of the appended independant patent claims.

Brief description of the drawings

The invention will be described in more detail in the following, reference being made to the accompanying drawings, in which:

- 5 FIG 1 is a partly fractioned side view of a device according to a preferred embodiment of the invention,
 FIG 2 is a partly exploded perspective view of the device according to FIG 1,
 FIGs 3 and 4 illustrate alternative embodiments of an
10 insert element used in the device,
 FIG 5 is a perspective view of a device according to an alternative embodiment of the invention,
 FIG 6 is a side view of the device according to FIG 5, and
15 FIG 7 is an exploded perspective view of the device according to FIGs 5 and 6.

Detailed description of the invention

A preferred embodiment of the device according to the
20 invention will now be described with reference to FIGs 1-4.

The device comprises a coin intake 10, suspension means 11,12, a drum 13 with perforations 14, a driving device 15 with a driving belt 16 belonging thereto, a collecting vessel 17, and a drum insert 18. The device is
25 arranged to be mounted by means of the suspension means 11,12 between the coin intake and a coin lifting device in a coin sorting and/or counting machine. The drum 13 is open at its respective ends, is connected at its first end to the coin intake 10, which in turn is connected to the coin
30 intake in the coin sorting and/or counting machine, and is connected at its second end to the coin lifting device in said machine. The drum 13, having a substantially circular cross section, is preferably made of e.g. metal or plastics and is according to the preferred embodiment horizontally

arranged, but may as an alternative be arranged at a certain downward or upward inclination.

An insert element 18 is arranged inside the drum 13, as indicated in FIG 1. In the exploded view according to
5 FIG 2 the insert element 18 is illustrated as being withdrawn from the drum 13, for reasons of clarity. Essentially, the insert element 18 has the shape of a so called Archimedes screw, which in essence may be described as a series of interconnected and substantially circular discs,
10 each of said discs being cut along the main portion of its diameter with a minor portion of each circle diameter being left uncut in order to keep the two circle halves together.

According to FIG 2 one circle half of each circle is vertically arranged (i.e. arranged in the radial direction
15 of the drum 13), while the second circle half is arranged at a certain angle with respect to the first circle half. Each vertical circle half is connected at its first end to the subsequent angled circle half and at its second end to the preceding angled circle half. The same is true for the
20 angled circle halves with respect to the vertical ones, with the exception, of course, of the outermost circle halves at the respective ends of the insert element 18. Depending on the distance discussed below between two vertical circle halves the angled half has a substantially
25 circular shape (a short distance), or an elliptic shape (a longer distance), respectively.

Preferably, the insert element 18 is manufactured of a relatively thin metal plate, and the insert element is firmly mounted on the inside of the drum 13 by for instance
30 soldering or welding.

As a consequence of the arrangement described above a number of cells or segments are formed by the insert element 18, each segment consisting of two vertical circle halves and an intermediate angled half (or, equivalently,
35 two angled halves and an intermediate vertical half). As a

result, when the drum 13 is rotated, a mass of coins deposited through the coin intake 10 is transported through the drum 13 thanks to the helical movement being performed by the insert element 18. However, during half of the revolution of the drum 13 and the insert element 18 the mass of coins is tumbled "on the spot" (i.e., substantially without movement in the transport direction), since one of the circle halves is vertically arranged, thereby blocking the mass of coins. This fact has the important effect of giving foreign objects - particularly elongated objects - an increased opportunity to arrange themselves in a direction suitable for separation through the perforations 14 of the drum 13, i.e. a radial direction with respect to the drum, and this effect will be described in more detail below.

The number of segments is important for several reasons. The more segments dividing an insert element of a certain length, the better the separation becomes of foreign objects, since these objects are exposed to more tumblings and are hence given a better opportunity to be separated. On the other hand, the transport velocity in the axial direction of the drum is decreased when the number of segments is increased. Furthermore, the distance between two subsequent vertical circle halves should be slightly longer than the diameter of the largest coin appearing in the coin system in question in order to avoid the risk of such a coin getting stuck. Trials have shown, that a distance of 45 mm between two vertical circle halves combined with four segments according to FIG 2, gives a very high probability of separation for the preferred embodiment of the invention, without the transport velocity decreasing to an unacceptably low level.

In FIG 3 there is shown an alternative design 19 of the insert element. In essence, the only difference compared to the insert element 18 described above is that

here, both of the circle or ellipse halves are angled to the same extent with respect to the radial direction of the drum. Such a design provides a smoother transport, since the mass of coins is now transported forward during the entire revolution of the drum. On the other hand, there is a loss to a certain extent of the tumbling effect which is periodically achieved according to the previous embodiment, and hence, the first embodiment 18 is currently regarded as the most suitable design to be used in the device according to the preferred embodiment, and this is true also from a manufacturing point of view.

In FIG 4 yet another embodiment 20 of the insert element is illustrated. Here, the insert element is helically formed from a wire- or strip-shaped element of for instance metal. However, the function is essentially the same as with the alternative 19 according to FIG 3.

The insert element 18 according to FIG 2 as well as the insert element 19 according to FIG 3 may be provided with fine perforations in order to avoid adhesion of wet coins or foreign objects to the surfaces of the insert element due to capillary forces.

Preferably, the drum perforations 14 are formed as round holes, the diameter of which is chosen to be slightly smaller than the smallest coin size acceptable to the coin handling machine in question.

As a driving device 15 preferably any previously known simple electrical motor is used, which is capable of driving the drum through the driving belt 16 in rotation around its longitudinal axis. The driving device 15 is responsive to a control signal for setting the rotational speed of the drum.

The operation and the function of the device according to the preferred embodiment of the invention will now be described.

A mass of coins, which may be unsorted and may contain foreign objects, is deposited by a customer into a coin intake in a machine for sorting and/or counting the coins in said mass of coins. The coin intake is connected
5 to the intake 10, the mass of coins thereby being supplied to the drum 13 through the intake 10. Through the rotation of the drum 13 by means of the driving device 15 the mass of coins is transported in a way described below through the drum from the coin intake to the coin lifting device,
10 which then forwards the coins to subsequent sorting and counting processes. Any foreign objects present in the mass of coins are separated during the transport in the drum through the drum perforations 14, and these objects are collected in the collecting vessel 17.

15 Foreign objects with an elongated shape, such as paper clips, hair pins, screws, etc, and with a length that exceeds the diameter of the perforations must be given a radial direction with respect to the cross section of the drum in order to be able to pass through the drum perfora-
20 tions, and hence the insert element 18 has been given its design as described above. In combination with the rotation of the drum the insert element exposes the transported mass of coins to a tumbling movement. Thus, the elongated foreign objects in the mass of coins are together with the
25 rest of the objects given a constantly varying direction thanks to the tumbling during the transport through the drum. Sooner or later during this transport such an elongated foreign object will get a radial direction with respect to the cross section of the drum and will hence
30 pass through the nearest perforation 6. "Valid" coins, which are accepted by the coin counting and sorting machine, can never be filtered out through the perforations, since the diameter of all such coins is larger than the diameter chosen for the perforations.

An important parameter when it comes to designing the device according to the invention is the length of the drum 13. More specifically, if the drum is too short, all foreign objects will not have the time to be separated during the transport through the drum. On the other hand, the drum may not be arbitrarily long, since the device should preferably fit inside a coin sorting and counting machine.

The diameter of the perforations is, as described above, also important, and so is the rotational speed of the drum.

A suitable perforation diameter is 13-16 mm for the preferred embodiment of the invention, but other values may also be appropriate.

An alternative embodiment of the device according to the present invention will now be described with reference to FIG 5-7.

In similarity to the above the device comprises a coin intake 30, suspension means 31, 32, a drum 33 with perforations 34 and a driving device 35. Even if this embodiment exhibits design differences as compared to the previously described preferred embodiment, the parts specified above according to FIGs 5-7 all have essentially the same function as the corresponding parts according to FIGs 1-4, and hence these parts are not described in more detail here.

One thing that differs, however, is that the drum 33 is now arranged in a downward slope towards the coin lifting device for reasons obvious from the following.

In FIG 6, reference numeral 39 indicates the drum angle with respect to the horizontal plane.

A number of carrier rails 38 are mounted on the inner wall of the drum 33, essentially in the axial direction of the drum. These rails, which preferably are made of metal or plastics, are preferably arranged with a certain dis-

placement in relation to each other in the axial direction of the drum, and they are bended at an obtuse angle at the end pointing away from the coin intake. A suggested design of the carrier rails 38 is illustrated more clearly in FIG

5 7.

Hence, the carrier rails 38 have replaced the insert element 18; 19; 20 described above, and an advantage with this approach is that the rails may be manufactured at a very low cost. The purpose of the rails is to expose the
10 mass of coins to a tumbling force when the drum 33 is rotated and to contribute to the transport of the mass of coins through the drum. Thanks to the downward slope of the drum according to the above the transport of the mass of coins is facilitated. In order to prevent elongated foreign
15 objects in particular to pass through the entire drum 33 without being separated, the rails 38 are as described above bended at the far end pointing towards the coin lifting device, thereby aiming at giving such foreign objects a direction suitable for separation through any of
20 the perforations 34.

As an alternative to this embodiment the inner wall of the drum is additionally provided with a number of members, not shown in the figures, which are formed as pins or edges protruding in an essentially radial direction.
25 These members also help in giving elongated foreign objects an orientation which is mainly orthogonal to the axial direction of the drum, thereby facilitating separation through the perforations.

An important parameter of the embodiment is the drum
30 inclination or angle 39 with respect to the horizontal plane. If the inclination is too steep, the mass of coins will be transported too quickly through the drum, thereby not letting all foreign objects to be separated. If the inclination is too small, difficulties arise when it comes

to transporting the mass of coins. In practice, an angle of inclination of about 10-15 degrees has proved suitable.

The driving device 15; 35 according to either of the embodiments described above is responsive to an external control signal for setting the rotational speed of the drum. Preferably, this external control signal is generated by a sensor in the coin lifting device, the control signal thereby having a nominal value, when the flow of coins into the coin lifting device - or, alternatively, the coin level in the device - lies within the limits of a successful handling of the coins for the coin lifting device and subsequent sorting and counting processes. In response to this nominal value of the control signal the driving means will drive the drum at a predetermined rotational speed according to the above, thereby obtaining a certain speed of coin flow. When the flow of coins reaches such a previously determined level, where the coin lifting device or any subsequent sorting and counting process is no longer able to handle all incoming coins successfully, but is rather risking to reach an over-filled condition, the control signal is given another value, wherein the driving device will detect the changed control signal and lower the rotational speed of the drum. As a consequence the coin flow speed will decrease, and the coin lifting device will be able to handle the superfluity of coins at the coin lifting device. When the level of coins in the coin lifting device returns below a predetermined level, the control signal is given its nominal value, the drum thereby returning to its normal rotational speed.

As an alternative, a sensor may be provided for measuring the drum speed. This sensor is operatively connected to a control unit capable of monitoring the momentary speed as detected by the sensor, thereby detecting an over-full or packed drum condition, since the speed will then have decreased below a predetermined value. When this

is the case, a control signal is supplied to the driving device 15; 35 for adjusting the rotational speed in a way similar to the one described above.

Hence, in this aspect, the device according to the invention has a function as a protection against over-
5 filling or a buffer receptacle. Within the scope of the invention the reduction described above of the rotational speed may be carried out in several steps, wherein the control signal may be given a corresponding number of
10 different values. Furthermore, the rotational speed may be reduced to a zero value, wherein the drum does not move, or to a negative value, wherein the drum is rotating in an opposite direction as compared to the normal direction. This is especially suitable to remedy such situations,
15 wherein elongated objects are in some way stuck in the drum, thereby obstructing the flow of coins.

According to yet another alternative embodiment of the invention, the drum is manufactured with an essentially polygonal cross section, such as a square shape or a hexagonal shape. Thanks to the angularity of this cross section
20 a mass of coins being transported through the rotating drum will be exposed to a tumbling force similar to the one described above for the embodiment according to FIGs 5-7. With a polygonal cross section of the drum the need for
25 separately mounted carrier rails 38 is consequently eliminated or reduced. The rest of the device according to this embodiment is essentially designed in accordance with the embodiments described above.

CLAIMS

1. A device for separating foreign objects from a mass of coins between a coin intake and a coin lifting device in a coin sorting and/or counting machine, characterized by a perforated drum (13; 33), said drum being arranged to rotate around its longitudinal axis, being open at its respective ends and being connected to the coin intake at a first end and to the coin lifting device at a second end; and by a driving device (15, 16; 35) for rotating the drum.

2. A device according to claim 1, further characterized by a drum insert (18; 19; 20; 38) for transporting and tumbling the mass of coins.

3. A device according to claim 1 or 2, characterized in that the drum (13; 33) has a substantially circular cross section.

4. A device according to claim 1 or 2, characterized in that the drum (13; 33) has a substantially polygonal cross section.

5. A device according to any preceding claim, characterized in that the drum insert (18; 19; 20) is helically formed on the inner wall of the drum (13).

6. A device according to claim 5, characterized in that the drum insert (18; 19) extends through a major part of the drum (13) length extension, the drum insert (18; 19) thereby together with the drum (13) forming a Archimedes screw.

7. A device according to claim 5,
c h a r a c t e r i z e d in that the drum insert (20) is
strip- or wire-shaped.

5 8. A device according to any of claims 1-4,
c h a r a c t e r i z e d in that the drum insert (38) is
constituted by a number of elongated carrier rails (38)
formed on the inner wall of the drum (33).

10 9. A device according to claim 8,
c h a r a c t e r i z e d in that at least some of the
rails (38) are displaced with respect to each other in the
axial direction of the drum (33).

15 10. A device according to claim 8 or 9,
c h a r a c t e r i z e d in that at least some of the
rails (38) are bended at an obtuse angle at an end pointing
away from the coin intake (30).

20 11. A device according to any preceding claim,
c h a r a c t e r i z e d in that the drum (13; 33) is
arranged at an angle (39) with respect to the horizontal
plane in a downward slope towards the coin lifting device.

25 12. A device according to any of claims 1-4 or 8-11,
c h a r a c t e r i z e d by a number of essentially
radially protuding pins or edges formed on the inner wall
of the drum (13; 33).

30 13. A method for separating foreign objects from a
mass of coins between a coin intake and a coin lifting
device in a coin sorting and/or counting machine,
c h a r a c t e r i z e d by the steps of
receiving the mass of coins at a first open end of a
35 perforated drum (13; 33),

rotating the drum (13; 33) around its longitudinal axis by means of a driving device (15, 16; 35),

successively transporting the coins through the rotation of the drum to a second open end of the drum, and

5 exposing the mass of coins and any foreign object(s) present therein to a tumbling force through the rotation of the drum, wherein said foreign object(s) is/are separated through the perforation (14; 34) of the drum.

10 14. A method according to claim 13,

characterized by the additional steps of obtaining information about the amount of coins in the coin lifting device arranged at the second open end of the drum (13; 33) and/or information about the rotational

15 speed of the drum, and

controlling the rotational speed of the drum and/or the rotational direction of the drum in response to said information.

20 15. Method of separating foreign objects from a mass of coins between a coin intake and a coin lifting device by means of the device according to any preceding claim, wherein the coins are successively transported by the rotating drum (13; 33) axially through the drum from the

25 coin intake to the coin lifting device, foreign objects being separated through the perforation (14; 34) of the drum, characterized in that the rotational speed of the drum (13; 33) is controlled in response to the amount of coins in the coin lifting device, so that the

30 rotational speed is reduced at a predetermined maximum amount of coins in the coin lifting device, thereby causing a reduction of the axial flow of coins through the drum.

1/3




FIG. 1







FIG. 2



3/3




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 96/00142

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: G07D 3/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: G07D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0091731 A2 (COMPUTER SERVICES CORPORATION), 19 October 1983 (19.10.83) --	1-15
A	US 2646805 A (C.F. ANDERSON), 28 July 1953 (28.07.53) --	1-15
A	US 3196887 A (R.B. WHITE, JR), 27 July 1965 (27.07.65) -- -----	1-15

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"Z" document member of the same patent family

Date of the actual completion of the international search

8 August 1996

Date of mailing of the international search report

09 -08- 1996

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Jan Silfverling
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

01/07/96

International application No.

PCT/SE 96/00142

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A2- 0091731	19/10/83	JP-C- 1390501	23/07/87
		JP-A- 58177186	17/10/83
		JP-B- 61055431	27/11/86
		US-A- 4535895	20/08/85
		US-A- 4779741	25/10/88
		JP-A- 58183972	27/10/83
		JP-B- 1002436	17/01/89
		JP-C- 1522717	12/10/89
		JP-A- 58186479	31/10/83
		JP-C- 1390506	23/07/87
		JP-A- 58186482	31/10/83
		JP-B- 61055432	27/11/86
		JP-C- 1390512	23/07/87
		JP-A- 58196878	16/11/83
		JP-B- 61055433	27/11/86
		JP-C- 1390513	23/07/87
		JP-A- 58196879	16/11/83
		JP-B- 61055434	27/11/86
US-A- 2646805	28/07/53	NONE	
US-A- 3196887	27/07/65	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.